

1. STANDARD APPLIANCES

BBT THERMOTECHNOLOGY LTD

Cotswold Way, Warndon, Worcester, Worcestershire WR4 9SW Tel: 01905 754624 Fax: 01905 754619 www.worcster-bosch.co.uk general.worcester@uk.bosch.com

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options			OFCERT License No
			H	W	D							
Camray 5	40/65	External	952	450	604	11.7-19	C2			Integral		
Camray 5	65/90	External	952	450	604	19-26.4	C2			Integral		
Danesmoor	12/14	Kitchen	C *	855	370	600	12-14	C2	T/F	CF	LLD	0005069602
Danesmoor	12/14	Kitchen	C *	855	370	600	12-14	C2	T/F		BF	0005069604
Camray 5	40/65	Kitchen		860	446	596	12-19	C2	F	100mm	CF	BF
Danesmoor	15/19	Kitchen	C *	855	370	600	15-19	C2/D	T/F	CF	LLD	0005039501
Danesmoor	15/19	Kitchen	C *	855	370	600	15-19	C2	T/F		RS	0005039605
Camray 5	65/90	Kitchen		860	446	596	19-26.5	C2	F	100mm	CF	BF
Danesmoor	20/25	Kitchen	C *	855	370	600	20-25	C2/D	T/F	CF	LLD	0005039603
Danesmoor	20/25	Kitchen	C *	855	370	600	20-25	C2	T/F		BF	0005039606
Camray 5	95/130	Kitchen		1000	508	704	28-38	C2	T	125mm	CF	BF
Danesmoor	26/32	Kitchen	C *	855	520	600	26-32	C2/D	T/F	CF	LLD	0005069725
Danesmoor	26/32	Kitchen	C *	855	520	600	26-32	C2	T/F		BF	0005039726
Camray 5	150/200	Kitchen		1060	555	796	43.9-58.6	C2	T/F	150mm	CF	180mm BF
Camray 5	200/240	Kitchen		1101	587	846	58.6-70.3	C2	T/F	150mm	CF	180mm BF
Greenstar Danesmoor	18/25	Kitchen		855	370	600	18-25	C2	T/F	CF		BF
Greenstar II HE	12/22	Kitchen		859	585	626	12-25	C2	T/F		BF	
Danesmoor	12/14	Utility	C *	855	370	600	12-14	C2	F	CF	LLD	0005039607
Danesmoor	12/14	Utility	C *	855	370	600	12-14	C2	T/F		BF	0005069610
Camray 5	40/65	Utility		860	446	596	12-19	C2	T/F	100mm	CF	BF
Danesmoor	15/19	Utility	C *	855	370	600	15-19	C2/D	F	CF	LLD	0005039608
Danesmoor	15/19	Utility	C *	855	370	600	15-19	C2	T/F		BF	0005069611
Camray 5	65/90	Utility		860	446	596	19-26.5	C2	T/F	100mm	CF	BF
Danesmoor	20/25	Utility	C *	855	370	600	20-25	C2/D	T	CF	LLD	0005039609
Danesmoor	20/25	Utility	C *	855	370	600	20-25	C2	T/F		BF	0005069612
Camray 5	95/130	Utility		1000	508	704	28-38	C2	T/F	125mm	CF	BF
Danesmoor	26/32	Utility		855	520	600	26-32	C2/D	T/F	CF	LLD	0005069727
Danesmoor	26/32	Utility		855	520	600	26-32	C2	T/F		BF	0005069728
Danesmoor	32/50	Utility		997	520	775	32-50	C2	T/F	CF		0005029831
Danesmoor	50/70	Utility	C *	997	520	935	50-70	C2	T/F	CF	LLD	0005029832
Greenstar Utility	18/25	Utility	A *	885	370	600	18-25	C2	T/F	CF	BF	
Greenstar Utility	32/50	Utility	A *	997	520	815	32-50	C2	T/F	CF	BF	
Greenstar Utility	50/70	Utility	A *	997	520	815	50-70	C2	T/F	CF	BF	
Worcester Bosch	50/70		C *	855	520	600	15-19	C2/D	T/F	CF	LLD	0005069613
Worcester Bosch	90/110			855	520	600	20-25	C2/D	T/F	CF	LLD	0005069614
Worcester Bosch	90/110		C *	855	520	600	26-32	C2/D	T/F	CF	LLD	0005069615

1. STANDARD APPLIANCES

FIREBIRD BOILERS LTD

Firebird UK, Unit 6, Westover Industrial Estate, Ivybridge, Devon PL21 9ES Tel: 01752 691131

Firebird Products, Hhean, Forkhill, Newry BT35 9SY www.firebird.ie Tel: 08230 888330 Fax: 02830 889096

Firebird Boilers Ltd, O'Donovan Enterprises, Ballymakeera, Co Cork, Ireland Tel: 00353 026 45253 Fax: 00353 026 45309

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options		OFCERT License No		
			H	W	D								
Firebird Popular	50/70	Boilerhouse	C *	740	390	355	14-21	C2/D	F	100mm	CF	0011020533	
Firebird Popular	70/90	Boilerhouse		740	390	355	21-26	C2/D	F	100mm	CF	0011020529	
Firebird Popular	90/120	Boilerhouse	C *	740	450	355	26-35	C2/D	F	125mm	CF	0011030515	
Firebird Popular	120/150	Boilerhouse	C *	810	460	415	35-44	C2/D	F	150mm	CF	0011020515	
Firebird Popular	150/200	Boilerhouse	C *	810	470	495	44-59	C2/D	F	150mm	CF	0011020509	
Firebird Popular	200/250	Boilerhouse	C *	580	520	540	59-73	C2/D	F	175mm	CF	0011020501	
Firebird Popular	250/310	Boilerhouse		885	575	660	73-91	C2/D	F	175mm	CF	BF	0011020536
Firebird Boilerhouse S	50/70	Boilerhouse	C *	740	390	355	14-21	C2	F	100mm	CF	BF	0011020534
Firebird Boilerhouse S	70/90	Boilerhouse	C *	740	390	355	21-26	C2	F	100mm	CF	BF	0011020530
Firebird Boilerhouse S	90/120	Boilerhouse	C *	740	450	355	26-35	C2	F	125mm	CF	BF	0011030516
Firebird Boilerhouse S	120/150	Boilerhouse	C *	810	460	415	35-44	C2	F	150mm	CF	BF	0011020516
Firebird Boilerhouse S	150/200	Boilerhouse	C *	810	470	495	44-59	C2	F	150mm	CF	BF	0011020510
Firebird Boilerhouse S	200/250	Boilerhouse	C *	850	520	540	59-73	C2	F	175mm	CF	BF	0011020502
Firebird Boilerhouse S	250/310	Boilerhouse		885	575	660	73-91	C2	F	175mm	CF	BF	0011020537
Firebird Roomsealed Popular	50/90	Hideaway	C *	845	390	570	14-26	C2	F			BF	0011020525
Firebird Roomsealed Popular	90/120	Hideaway	C *	845	450	585	26-35	C2	F			BF	0011030517
Firebird Roomsealed Popular	120/150	Hideaway	C *	1050	442	705	35-44	C2	F			BF	0011020517
Firebird Roomsealed Popular	150/200	Hideaway		1055	462	790	44-59	C2	F			BF	0011020511
Firebird Roomsealed Popular	200/250	Hideaway		960	510	885	59-73	C2	F			BF	0011020504
Firebird Roomsealed Popular	250/310	Hideaway		1015	580	930	73-91	C2	F			BF	0011020538
Firebird S Kitchen	50/70	W/C Indoor		845	380	595	14-21	C2/D	F	100mm	CF	BF	
Firebird S Kitchen	70/90	W/C Indoor		845	380	595	21-26	C2/D	F	100mm	CF	BF	
Firebird S Kitchen	90/120	W/C Indoor		840	440	595	36-35	C2/D	F	125mm	CF	BF	0011030518
Firebird S Kitchen	120/150	W/C Indoor		1050	442	705	35-44	C2/D	F	150mm	CF	BF	
Firebird S Kitchen	150/200	W/C Indoor		1055	462	790	44-59	C2/D	F	150mm	CF	BF	
Firebird S Kitchen	200/250	W/C Indoor		960	510	885	59-73	C2/D	F	175mm	CF	BF	0011020503
Firebird S Kitchen	250/310	W/C Indoor		1015	580	930	73-91	C2/D	F	175mm	CF	BF	0011020542
Roomsealed Super Q	50/90	W/C Indoor		835	610	590	14-26	C2	F			BF	0011020527
Roomsealed Super Q	90/120	W/C Indoor		850	680	590	26-35	C2	F			BF	
Roomsealed Super Q	120/150	W/C Indoor		1050	442	705	35-44	C2/D	F	150mm	CF	BF	0011020520
Roomsealed Super Q	150/200	W/C Indoor		1055	462	790	44-59	C2/D	F	150mm	CF	BF	0011020513
Roomsealed Super Q	200/250	W/C Indoor		960	510	885	59-73	C2/D	F	175mm	CF	BF	0011020507
Roomsealed Super Q	250/310	W/C Indoor		1015	580	930	73-91	C2/D	F	175mm	CF	BF	0011020540
Heatpac 90	50/90	Outdoor		945	655	625	14-26	C2	F		Turret Flue	LLD	0011030504
Heatpac 120	90/120	Outdoor	C *	945	710	625	26-35	C2	F		Turret Flue	LLD	
Heatpac 150	120/150	Outdoor	C *	1010	720	735	35-44	C2	F		Turret Flue	LLD	0011020501
Heatpac 200	150/200	Outdoor	C *	1025	895	860	44-59	C2	F		Turret Flue	LLD	0011020521
Heatpac 250	200/250	Outdoor	C *	1025	895	860	59-73	C2	F		Turret Flue	LLD	0011020514

1. STANDARD APPLIANCES

FIREBIRD BOILERS LTD (Continued)

Firebird UK, Unit 6, Westover Industrial Estate, Ivybridge, Devon PL21 9ES Tel: 01752 691131

Firebird Products, Hhean, Forkhill, Newry BT35 9SY www.firebird.ie Tel: 08230 888330 Fax: 02830 889096

Firebird Boilers Ltd, O'Donovan Enterprises, Ballymakeera, Co Cork, Ireland Tel: 00353 026 45253 Fax: 00353 026 45309

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options	OFCERT License No	
			H	W	D						
Heatpac310	250/310		1125	950	960	73-91	C2	F	Turret Flue	LLD	0011020508
Heatpac 70 Slimline	50/70		925	760	410	14-21	C2	F	Side Flue	LLD	0011020541
Heatpac 90 Slimline	70/90		925	760	410	21-26	C2	F	Side Flue	LLD	0011030502
Heatpac 90 S	50/90		945	655	625	14-26	C2	F	Side Flue	LLD	0011030503
Heatpac 120 S	90/120	C *	945	710	625	26-35	C2	F	Side Flue	LLD	0011020528
Heatpac 90	70/90								Turret Flue		0011030514

GRANT ENGINEERING LTD

Crinkle, Birr, Offaly Ireland grantengineering@eir.net Tel: 00353 (0) 509 20089 Fax: 00353 (0) 509 21060

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options	OFCERT License No
			H	W	D					
Euroflame	50/70	Kitchen/Utility	C *	812	345	555	15-21	C2/D	T	100mm
Euroflame	50/70	Kitchen/Utility	C *	812	345	555	15-21	C2/D	T	
Euroflame	50/90	Kitchen/Utility		860	410	600	15-26	C2/D	T	100mm
Euroflame	50/90	Kitchen/Utility		860	410	600	15-26	C2/D	T	
Euroflame	90/120	Kitchen/Utility	C *	860	410	600	26-35	C2/D	T	125mm
Euroflame	90/120	Kitchen/Utility	C *	860	410	600	26-35	C2/D	T	100mm
Euroflame	50/70	Boilerhouse	C *	695	345	555	15-21	C2/D	T	
Euroflame	50/70	Boilerhouse	C *	695	345	555	15-21	C2/D	T	100mm
Euroflame	50/90	Boilerhouse		750	425	620	15-26	C2/D	T	
Euroflame	50/90	Boilerhouse		750	425	620	15-26	C2/D	T	125mm
Euroflame	90/120	Boilerhouse	C *	715	425	620	26-35	C2/D	T	
Euroflame	90/120	Boilerhouse	C *	715	425	620	26-35	C2/D	T	125mm
Euroflame	50/70	Outdoor	C *	840	740	388	15-21	C2/D	T	
Euroflame	50/90	Outdoor		930	800	460	15-26		T	150mm
Euroflame	50/90	Outdoor		930	800	460	15-26	C2/D	T	
Euroflame	90/120	Outdoor	C *	930	800	460	26-35		T	100mm
Euroflame	90/120	Outdoor	C *	930	800	460	26-35	C2/D	T	
Multipass	50/70	Kitchen	C *	860	410	605	15-21	C2/D	F	125mm
Multipass	50/70	Kitchen	C *	860	410	605	15-21	C2/D	F	
Multipass	70/90	Kitchen	C *	860	410	605	21-26	C2/D	F	125mm
Multipass	70/90	Kitchen	C *	860	410	605	21-26	C2/D	F	
Multipass	90/140	Kitchen		1080	410	690	26-41	C2/D	F	150mm
Multipass	90/140	Kitchen		1080	530	690	26-41	C2/D	F	
Multipass	140/160	Kitchen	C *	1175	530	835	41-47	C2/D	F	

1. STANDARD APPLIANCES

GRANT ENGINEERING LTD (Continued)

Crinkle, Birr, Offaly Ireland grantengineering@eir.net Tel: 00353 (0) 509 20089 Fax: 00353 (0) 509 21060

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options	OFCERT License No
			H	W	D					
Multipass	140/160	Kitchen	C *	1175	530	835	41-47	C2/D	F	125mm
Multipass	160/200	Kitchen	C *	1175	530	835	47-48	C2/D	F	BF
Multipass	160/200	Kitchen	C *	1175	530	835	47-58	C2/D	F	100mm CF
Multipass	70/90	Boilerhouse	C *	720	460	625	21-26	C2/D	F	BF
Multipass	70/90	Boilerhouse	C *	720	460	625	21-26	C2/D	F	125mm BF
Multipass	90/140	Boilerhouse		895	460	655	26-41	C2/D	F	
Multipass	90/140	Boilerhouse		895	460	655	26-41	C2/D	F	125mm
Multipass	140/160	Boilerhouse	C *	1000	550	765	41-47	C2/D	F	
Multipass	140/160	Boilerhouse	C *	1000	550	765	41-47	C2/D	F	150mm
Multipass	160/200	Boilerhouse	C *	1000	550	765	47-58	C2/D	F	
Multipass	160/200	Boilerhouse	C *	1000	550	765	47-58	C2/D	F	LLD
Multipass	110/140	Outdoor	C *	930	843	466	32-41	C2	F	125mm
Multipass	110/140	Outdoor	C *	930	843	466	32-41	C2/D	F	

GRANT ENGINEERING (UK) LIMITED

Hopton House, Hopton Industrial Estate, Devizes, Wiltshire SN10 2EU Tel: 01380 736920 Fax: 01380 736920 www.grantuk.com info@grantuk.com

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options	OFCERT License No
			H	W	D					
VTXECO1521	Utility	A	860	430	605	15-21	C2	F	BF	CF
VTXECO2126	Utility	A	860	430	605	21-26	C2	F	BF	CF
VTXECO2635	Utility	A	900	470	603	26-35	C2	F	BF	CF
VTXOMECO1521	External	A	908	505	1005	15-21	C2	E	BF	CF
VTXOMECO2126	External	A	908	505	1005	21-26	C2	E	BF	CF
VTXOMECO2635	External	A	908	505	1005	26-35	C2	E	BF	CF
VTXWH1216	Wall Hung	A	850	580	322	12-16	C2	F	BF	CF
VTXWH1621	Wall Hung	A	850	580	322	16-21	C2	F	BF	CF
VTXOMWH1216	External Wall Hung	A	837	635	366	12-16	C2	E	BF	CF
VTXOMWH1621	External Wall Hung	A	837	635	366	16-21	C2	E	BF	CF
VTX1521	Kitchen/Utility	A	855	348	566	15-21	C2	F	BF	CF
VTX1526	Kitchen/Utility	A	860	470	603	15-26	C2	F	BF	CF
VTX2636	Kitchen/Utility	A	900	470	603	26-36	C2	F	BF	CF
VTX3646	Kitchen/Utility	A	900	470	603	36-46	C2	F	BF	CF
VTX4658	Kitchen/Utility	A	1234	563	786	46-58	C2	F	BF	CF
VTX5870	Kitchen/Utility	A	1234	563	786	58-70	C2	F	BF	CF
VTXOM1521	External	A	879	385	943	15-21	C2	E	BF	CF
VTXOM1526	External	A	908	505	1005	15-26	C2	E	BF	CF
VTXOM2636	External	A	908	505	1005	26-36	C2	E	BF	CF
VTXOM3646	External	A	908	505	1005	36-46	C2	E	BF	CF

1. STANDARD APPLIANCES

MISTRAL BOILERS LTD

Unit C3, Halesfield 23, Telford, Shropshire TF7 4NY Tel: 01952 270082 Fax: 01952 270086

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options		OFCERT License No
			H	W	D						
CKUT1 15/20	15/20 Kitchen/Utility	A	865	495	600	15-20	C2	F	100-125mm	CF	BF
CKUT2 20/26	20/26 Kitchen/Utility	A	865	495	600	20-26	C2	F	100-125mm	CF	BF
CKUT3 26/35	26/35 Kitchen/Utility	A	865	495	600	26-35	C2	F	125mm	CF	BF
CKUT4 35/41	35/41 Kitchen/Utility	A	865	495	600	35-41	C2	F	125mm	CF	BF
CKUT5 41/50	41/50 Kitchen/Utility	A	1230	500	755	41-50	C2	F	150mm	CF	BF
CKUT6 50/58	50/58 Kitchen/Utility	A	1230	500	755	50-58	C2	F	150mm	CF	BF
CKUT7 58/68	58/68 Kitchen/Utility	A	1230	500	755	58-68	C2	F	150mm	CF	BF
COD1 15/20	15/20 Outdoor	A	895	770	680	15-20	C2	F	100-125mm	CF	BF
COD2 20/26	20/26 Outdoor	A	895	770	680	20-26	C2	F	100-125mm	CF	BF
COD3 26/35	26/35 Outdoor	A	895	770	680	26-35	C2	F	125mm	CF	BF
COD4 25/41	35/41 Outdoor	A	895	770	680	35-41	C2	F	125mm	CF	BF
COD5 41/50	41/50 Outdoor	A	1245	605	675	41-50	C2	F	150mm	CF	BF
COD6 50/58	50/58 Outdoor	A	1245	605	675	50-58	C2	F	150mm	CF	BF
COD7 58/68	58/68 Outdoor	A	1245	605	675	58-68	C2	F	150mm	CF	BF
CBH1 15/20	15/20 Boilerhouse	A	865	495	600	15-20	C2	F	100-125mm	CF	BF
CBH2 20/26	20/26 Boilerhouse	A	865	495	600	20-26	C2	F	100-125mm	CF	BF
CBH3 26/35	26/35 Boilerhouse	A	865	495	600	26-35	C2	F	125mm	CF	BF
CBH4 35/41	35/41 Boilerhouse	A	865	495	600	35-41	C2	F	125mm	CF	BF
CBH5 41/50	41/50 Boilerhouse	A	1230	500	755	41-50	C2	F	150mm	CF	BF
CBH6 50/58	50/58 Boilerhouse	A	1230	500	755	50-58	C2	F	150mm	CF	BF
CBH7 58/68	58/68 Boilerhouse	A	1230	500	755	58-68	C2	F	150mm	CF	BF
KUT1 50/70	50/70 Kitchen/Utility	C	865	495	600	15-20	C2	F	100-125mm	CF	BF
KUT2 70/90	70/90 Kitchen/Utility	C	865	495	600	20-26	C2	F	100-125mm	CF	BF
KUT3 90/120	90/120 Kitchen/Utility	C	865	495	600	26-35	C2	F	125mm	CF	BF
KUT4 120/140	120/140 Kitchen/Utility	C	865	495	600	35-41	C2	F	125mm	CF	BF
KUT5 140/170	140/170 Kitchen/Utility	C	1230	500	755	41-50	C2	F	150mm	CF	BF
KUT6 170/200	170/200 Kitchen/Utility	C	1230	500	755	50-58	C2	F	150mm	CF	BF
KUT7 200/232	200/232 Kitchen/Utility	C	1230	500	755	58-68	C2	F	150mm	CF	BF
OD1 50/70	50/70 Outdoor	C	895	770	680	15-20	C2	F	100-125mm	CF	BF
OD2 70/90	70/90 Outdoor	C	895	770	680	20-26	C2	F	100-125mm	CF	BF
OD3 90/120	90/120 Outdoor	C	895	770	680	26-35	C2	F	125mm	CF	BF
OD4 120/140	120/140 Outdoor	C	895	770	680	35-41	C2	F	125mm	CF	BF
OD5 140/170	140/170 Outdoor	C	1245	605	675	41-50	C2	F	150mm	CF	BF
OD6 170/200	170/200 Outdoor	C	1245	605	675	50-58	C2	F	150mm	CF	BF
OD7 200/232	200/232 Outdoor	C	1245	605	675	58-68	C2	F	150mm	CF	BF
BH1 50/70	50/70 Boilerhouse	C	865	495	600	15-20	C2	F	100-125mm	CF	BF
BH2 70/90	70/90 Boilerhouse	C	865	495	600	20-26	C2	F	100-125mm	CF	BF
BH3 90/120	90/120 Boilerhouse	C	865	495	600	26-35	C2	F	125mm	CF	BF

1. STANDARD APPLIANCES

MISTRAL BOILERS LTD (Continued)

Unit C3, Halesfield 23, Telford, Shropshire TF7 4NY Tel: 01952 270082 Fax: 01952 270086

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options			OFCERT License No
			H	W	D							
BH4 120/140	120/140 Boilerhouse	C	865	495	600	35-41	C2	F	125mm	CF	BF	
BH5 140/170	140/170 Boilerhouse	C	1230	500	755	41-50	C2	F	150mm	CF	BF	
BH6 170/200	170/200 Boilerhouse	C	1230	500	755	50-58	C2	F	150mm	CF	BF	
BH7 200/232	200/232 Boilerhouse	C	1230	500	755	58-68	C2	F	150mm	CF	BF	

TRIANCO HEATING PRODUCTS LTD

Thornccliffe, Chapeltown, Sheffield S35 www.trianco.co.uk info@trianco.co.uk Tel: 0114 245 3021 Fax: 0114 245 3021

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options			OFCERT License No
			H	W	D							
EuroStar Utility	50/60	Kitchen	855	400	600	14.7-19.1	C2	F	100mm	125mm	CF	
EuroStar Utility	50/60	Kitchen	855	400	600	14.7-19.1	C2	F	100mm	125mm	BF	
EuroStar Utility	70/90	Kitchen	C *	855	460	600	20.6-26.5	C2	F	100mm	125mm	CF
EuroStar Utility	70/90	Kitchen	C *	855	460	600	20.6-26.5	C2	F	100mm	125mm	BF
EuroStar Utility	100/125	Kitchen	C *	900	460	650	29.4-36.8	C2	T F		125mm	CF
EuroStar Utility	100/125	Kitchen	C *	900	460	650	29.4-36.8	C2	T F		125mm	BF
EuroStar Utility	130/150	Utility	C *	1040	512	825	38.2-44.1	C2	T F		150mm	CF
EuroStar Utility	130/150	Utility	C *	1040	512	825	38.2-44.1	C2	T F		150mm	BF
EuroStar Utility	160/180	Utility	C *	1040	512	825	47.1-52.9	C2	T F		150mm	CF
EuroStar Utility	160/180	Utility	C *	1040	512	825	47.1-52.8	C2	T F		150mm	BF
EuroStar Utility	190/240	Utility	C *	1040	512	825	55.9-70.6	C2	T F		150mm	CF BF
EuroStar Utility	190/240	Utility	C *	1040	512	825	55.9-70.6	C2	T F		150mm	CF BF
EuroStar 2000	50/65	Kitchen	C *	860	400	600	14.7-19.1	C2	F	100mm	125mm	CF
EuroStar 2000	50/65	Kitchen	C *	860	400	600	14.7-19.1	C2	F	100mm	125mm	BF
EuroStar 2000	70/90	Kitchen	C *	860	460	600	20.5-26.3	C2	F	100mm	125mm	CF
EuroStar 2000	70/90	Kitchen	C *	860	460	600	20.5-26.3	C2	F	100mm	125mm	BF
EuroStar Utility System	50/90	Kitchen	C *	860	460	600	20.5-26.3	C2	F	100mm	125mm	CF
EuroStar Utility System	50/90	Kitchen	C *	860	460	600	14.6-26.3	C2	F	100mm	125mm	BF
EuroStar External	50/90		C *	920	500	1015	14.6-26.3	C2	F		Integral Flue	
EuroStar External	95/115		C *	980	500	1075	27.9-33.8	C2	F		Integral Flue	
EuroStar Eurotrader	50/90	Boilerhouse	C *	640	455	360	14.6-26.3	C2	F	100mm	125mm	CF
EuroStar Eurotrader	50/90	Boilerhouse	C *	640	455	360	14.6-26.3	C2	F	100mm	125mm	BF
EuroStar Eurotrader	100/125	Boilerhouse	C *	710	455	440	29.4-36.8	C2	T F		125mm	CF
EuroStar Eurotrader	100/125	Boilerhouse	C *	710	455	440	29.4-36.8	C2	T F		125mm	BF
Trianco Contractor	50/90	Utility	C *	860	460	600	14.6-26.3	C2	F	100mm	125mm	CF
Trianco Contractor	50/90	Utility	C *	860	460	600	14.6-26.3	C2	F	100mm	125mm	BF
Trianco Contractor	100/125	Utility	C *	900	460	650	29.4-36.8	C2	F		125mm	CF
Trianco Contractor	100/125	Utility	C *	900	460	650	29.4-36.8	C2	F		125mm	BF

1. STANDARD APPLIANCES

WARMFLOW ENGINEERING CO LTD

Moira Road, Lisburn, Co Antrim BT28 2RF sales@warmflow.co.uk Tel: 082 9262 1515 Fax: 028 9262 0869

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options	OFCERT License No
			H	W	D					
Bluebird	200BB	Boilerhouse	970	490	530	58.6	C2/D	T	125mm	CF BF
Bluebird	250BB	Boilerhouse	970	490	530	73	C2/D	T	150mm	CF
Bluebird	300	Boilerhouse	1313	864	864	88	C2/D	T F	200mm	CF
Bluebird	400	Boilerhouse	1313	974	974	117.2	C2/D	T F	200mm	CF
Bluebird	500	Boilerhouse	1570	1085	1085	146.6	C2/D	T F	200mm	CF
Whitebird	200WB	Utility	1065	495	775	58.6	C2/D	T	125mm	CF BF
Kabin Pak	50/70	Outdoor	892	732	626	14.6-20.5	C2/D	T	125mm	CF LLD
Kabin Pak	50/90	Outdoor	925	398	784	14.7-26.4	C2/D	T	125mm	CF LLD
Kabin Pak	70/90	Outdoor	892	732	626	20.5-26.4	C2/D	T	125mm	CF LLD
Kabin Pak	90/120	Outdoor	892	942	626	26.4-35.2	C2/D	T	125mm	CF LLD
Kabin Pak	120/150	Outdoor	1089	902	836	35.2-44	C2/D	T	125mm	CF LLD
Kabin Pak	200	Outdoor	1089	902	836	58.6	C2/D	T	125mm	CF LLD

NOTE: All boilers including Kabin Paks fitted with a low level discharge or balanced flue must burn kerosene

1. SYSTEM APPLIANCES

BBT THERMOTECHNOLOGY LTD

Cotswold Way, Warndon, Worcester, Worcestershire WR4 9SW Tel: 01905 754624 Fax: 01905 754619 www.worcster-bosch.co.uk general.worcester@uk.bosch.com

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options			OFCERT License No
			H	W	D							
Camray 5	40/65	System	860	446	596	12-19	C2	F	100mm	CF	BF	0001039943
Camray 5	65/90A	System	860	446	596	19-26.5	C2	F	100mm	CF	BF	
Camray 5	95/130A	System	1000	508	704	28-38	C2	T	125mm	CF	BF	
Classic	50/70A	System	860	405	600	15-20	C2	T	100mm	CF	BF	
Classic	70/90A	System	860	470	600	20-26.5	C2	T	100mm	CF	BF	
Classic	95/130	System	1000	508	705	28-38	C2	T	125mm	CF	BF	0001100053
Danesmoor	12/14	System	C *	855	370	600	14-14	C2	T F	CF	LLD	0005069616
Danesmoor	12/14	System	C *	855	370	600	12-14	C2	T F		RS	0005069619
Danesmoor	15/19	System	C *	855	370	600	15-19	C2/D	T F	CF	LLD	0005069617
Danesmoor	15/19	System	C *	855	370	600	15-19	C2	T F		RS	0005069620
Danesmoor	20/25	System	C *	855	370	600	20-25	C2/D	T F	CF	LLD	0005069618
Danesmoor	20/25	System	C *	855	370	600	20-25	C2	T F		RS	0005069621

FIREBIRD BOILERS LTD

Firebird UK, Unit 6, Westover Industrial Estate, Ivybridge, Devon PL21 9ES Tel: 01752 691131

Firebird Products, Hhean, Forkhill, Newry BT35 9SY www.firebird.ie Tel: 08230 888330 Fax: 02830 889096

Firebird Boilers Ltd, O'Donovan Enterprises, Ballymakeera, Co Cork, Ireland Tel: 00353 026 45253 Fax: 00353 026 45309

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options			OFCERT License No	
			H	W	D								
Firebird Sealed Systems	50/70	W/C Indoor		840	505	600	14-21	C2/D	F	100mm	CF	BF	0011020543
Firebird Sealed Systems	70/90	W/C Indoor	C *	840	505	600	21-26	C2/D	F	100mm	CF	BF	0011020544
Firebird Sealed Systems	90/120	W/C Indoor		840	545	600	26-35	C2/D	F	125mm	CF	BF	0011030522
Firebird Sealed Systems	120/150	W/C Indoor		1050	560	705	35-44	C2/D	F	150mm	CF	BF	0011030523
Heatpac 90 System	70/90	Outdoor		945	655	625	21-26	C2	F		Turret Flue	LLD	0011030506
Heatpac 120 System	90/120	Outdoor		945	710	625	26-35	C2	F		Turret Flue	LLD	0011030507
Heatpac 150 System	120/150	Outdoor		1010	720	690	35-44	C2	F		Turret Flue	LLD	0011030508
Heatpac 70 Slimline System	50/70	Outdoor		925	760	410	14-21	C2	F		Side Flue	LLD	0011030509
Heatpac 90 Slimline System	70/90	Outdoor		925	760	410	21-26	C2	F		Side Flue	LLD	0011030510

1. SYSTEM APPLIANCES

GRANT ENGINEERING LTD

Crinkle, Birr, Offaly Ireland grantengineering@eir.net Tel: 00353 (0) 509 20089 Fax: 00353 (0) 509 21060

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options		OFCERT License No		
			H	W	D								
Euroflame	50/90	System	C *	860	410	600	15-26	C2/D	T	100mm	CF	0002029603	
Euroflame	50/90	System	C *	590	410	600	15-26	C2/D	T		BF	LLD	0002089719
Euroflame	90/120	System		860	410	600	26-35	C2/D	T	125mm	CF		
Euroflame	90/120	System		860	410	600	26-35	C2/D	T		BF	LLD	
Multipass	50/70	System	C *	860	410	605	15-21	C2/D	F	100mm	CF		
Multipass	50/70	System	C *	860	410	605	15-21	C2/D	F		BF	LLD	
Multipass	70/90	System	C *	860	410	605	21-26	C2/D	F	100mm	CF		
Multipass	70/90	System	C *	860	410	605	21-26	C2/D	F		BF	LLD	
Multipass	90/140	System		1080	410	690	26-41	C2/D	F	125mm	CF		
Multipass	90/140	System		1080	410	690	26-41	C2/D	F		BF	LLD	
Euroflame	50/70	Outdoor System		840	740	388	15-21	C2/D	T			LLD	
Euroflame	50/70	Outdoor System		840	740	388	15-21	C2/D	T	100mm	CF		
Euroflame	70/90	Outdoor System		930	800	460	21-26	C2	T			LLD	
Euroflame	70/90	Outdoor System		930	800	460	21-26	C2/D	T	100mm	CF		
Euroflame	90/120	Outdoor System		930	800	460	26-35	C2	T			LLD	
Euroflame	90/120	Outdoor System		930	800	460	26-35	C2/D	T	125mm	CF		
Multipass	110/140	Outdoor System		930	843	466	32-41	C2	F			LLD	
Multipass	110/140	Outdoor System		930	843	466	32-41	C2/D	F	125mm	CF		

GRANT ENGINEERING (UK) LIMITED

Hopton House, Hopton Industrial Estate, Devizes, Wiltshire SN10 2EU Tel: 01380 736920 Fax: 01380 736920 www.grantuk.com info@grantuk.com

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options		OFCERT License No
			H	W	D						
VTXSWH1216	Wall Hung System	A	850	580	322	12-16	C2	F/T	CF	BF	
VTXSWH1621	Wall Hung System	A	850	580	322	16-21	C2	F/T	CF	BF	
VTXSOMWH1216	External Wall Hung System	A	837	635	366	12-16	C2	E	CF	BF	
VTXSOMWH1621	External Wall Hung System	A	837	635	366	16-21	C2	E	CF	BF	
VTXS1526	Kitchen/Utility System	A	860	470	603	15-26	C2	F/T	CF	BF	
VTXS2636	Kitchen/Utility System	A	900	470	603	26-36	C2	F/T	CF	BF	
VTXS3646	Kitchen/Utility System	A	900	470	603	36-46	C2	F/T	CF	BF	

1. SYSTEM APPLIANCES

MISTRAL BOILERS LTD

Unit C3, Halesfield 23, Telford, Shropshire TF7 4NY Tel: 01952 270082 Fax: 01952 270086

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options		OFCERT License No
			H	W	D						
CS1 15/20	15/20 Sealed System Kitchen	A	865	495	600	15-20	C2	F	100-125mm	CF	BF
CS2 20/26	20/26 Sealed System Kitchen	A	865	495	600	20-26	C2	F	100-125mm	CF	BF
CS3 26/35	26/35 Sealed System Kitchen	A	865	495	600	26-35	C2	F	125mm	CF	BF
CS4 35/41	35/41 Sealed System Kitchen	A	865	495	600	35-41	C2	F	125mm	CF	BF
CODSS1 15/20	15/20 Sealed System Outdoor	A	895	770	680	15-20	C2	F	100-125mm	CF	BF
CODSS2 20/26	20/26 Sealed System Outdoor	A	895	770	680	20-26	C2	F	100-125mm	CF	BF
CODSS3 26/35	26/35 Sealed System Outdoor	A	895	770	680	26-35	C2	F	125mm	CF	BF
CODSS4 35/41	35/41 Sealed System Outdoor	A	895	770	680	35-41	C2	F	125mm	CF	BF
S1 50/70	50/70 Sealed System Kitchen	C	865	495	600	15-20	C2	F	100-125mm	CF	BF
S2 70/90	70/90 Sealed System Kitchen	C	865	495	600	20-26	C2	F	100-125mm	CF	BF
S3 90/120	90/120 Sealed System Kitchen	C	865	495	600	26-35	C2	F	125mm	CF	BF
S4 120/140	120/140 Sealed System Kitchen	C	865	495	600	35-41	C2	F	125mm	CF	BF
ODSS1 50/70	50/70 Sealed System Outdoor	C	895	770	680	15-20	C2	F	100-125mm	CF	BF
ODSS2 70/90	70/90 Sealed System Outdoor	C	895	770	680	20-26	C2	F	100-125mm	CF	BF
ODSS3 90/120	90/120 Sealed System Outdoor	C	895	770	680	26-35	C2	F	125mm	CF	BF
ODSS4 120/140	35/41 Sealed System Outdoor	C	895	770	680	35-41	C2	F	125mm	CF	BF

WARMFLOW ENGINEERING CO LTD

Moir Road, Lisburn, Co Antrim BT28 2RF sales@warmflow.co.uk Tel: 082 9262 1515 Fax: 028 9262 0869

Product Name	Model	SEDBUK Efficiency	Dimensions (mm)			Output kW	Fuel C2/D	SERV Access	Flue Options		OFCERT License No
			H	W	D						
S70	Utility/Kitchen		865	413	600	14.7-20.5	C2/D	F	125mm	CF	BF
S90	Utility/Kitchen		865	413	600	20.5-26.4	C2/D	F	125mm	CF	BF
50/70 SKP	Outdoor		892	732	636	20.5-26.4	C2/D	F	125mm	CF	LLD
70/90 SKP	Outdoor		891	732	636	20.5-26.4	C2/D	F	125mm	CF	LLD